EXTERNAL CAVITY WALLS.

1-FACING BRICK

EXTERNAL LEAF EXTERNAL LEAF TO BE 100MM NOMINAL FACING BRICKS (SUBJECT PLANNING APPROVAL) TO BS 3921 LAID IN WITH WHITE CÒLOURED MORTAR.

CAVITY TO BE NOMINAL 100MM AS SHOWN ON G.A. CAVITIES TO BE CLOSED AT EAVES AND VERGES. BOTH SKINS TO BE TIED AT 450MM CENTRES VERTICALLY AND 900MM CENTRES HORIZONTALLY, WITH STAINLESS STEEL TIES TO BS 1243, ADDITIONAL TIES TO BE PROVIDED AT ALL DOOR AND WINDOW REVEALS @ 225MM CENTRES.(EVERY BLOCK COURSE)

CAVITY INSULATION.

CAVITIES TO BE FULLY FILLED WITH 100MM THICK "ISOWOOL 32"CAVITY INSULATION CAVITY INSULATION TO MANUFACTURERS REQUIREMENT AND SPECIFICATION. INSULATION TO BE TAKEN 215MM MINIMUM BELOW UNDER SIDE OF SLAB. CAVITY AROUND EXTERNAL OPENINGS TO BE CLOSED WITH APPROVED INSULATED CAVITY CLOSER.

INTERNAL LEAF TO BE 100MM LIGHTWEIGHT THERMALITE BLOCK (SHIELD) ABOVE TO HAVE A MINIMUM COMPRESSIVE STRENGTH OF 3.6 N/MM2

WALLS TO BE FINISHED WITH 12.5MM PLASTERBOARD ON DABS, WITH CONTINUOUS BAND AT PERIMETERS AND AROUND OPENINGS INCLUDING ELECTRICAL SOCKETS, AIR BRICKS, ETC.

INTERNAL PARTITIONS.

A)-BLOCK PARTITIONS.

100MM LIGHTWEIGHT CONCRETE BLOCK WITH A MINIMUM COMPRESSIVE STRENGTH OF 3.6 N/MM2. WITH DRY LINING FINISH. 12.5MM THICK GYPSUM WALLBOARD ON DABS TO BOTH SIDE WALLS WITH SKIM FINISH.

B)-STUD PARTITIONS & BRACING PARTITIONS

- 70 50 "C" METAL STUDS AT 600MM CENTRES WITH HEAD AND SOLE PLATES. PROVIDE DOUBLE STUDS AROUND DOOR OPENINGS, PROVIDE 50MM THICK ISOVER ACOUSTIC ROLL (APR 1200) INSULATION BETWEEN STUDS. BOTH SIDE OF STUD WALLS TO BE LINED WITH 12.5MM THICK GYPSUM WALLBOARD WITH SEALED JOINTS AND SKIM FINISH.

INTERNAL SIDES OF PARTITIONS (FACING SHOWER CUBICAL/BATH) TO EN SUITE OR BATHROOM TO BE LINED WITH 12MM THICK MOISTURE

RESISTANCE PLASTERBOARD AND PAINTED WITH T2MM HAPPROVED WATERPROOFING COMPOUND PRIOR TO TILING. WHERE BATHROOM/EN-SUITE UNITS, RADIATORS OR KITCHEN/UTILITY UNITS ARE TO BE FIXED TO THE METAL STUD WALLS, PROVIDE AND FIX 12MM PLY BETWEEN METAL STUD TO THE FIXING SIDE OF STUD WALL.

2- BRACING PARTITIONS- SEE DRAWING NUMBER DET-01-08 FOR CONSTRUCTION DETAILS

GROUND FLOOR CONSTRUCTION 1- HOUSES

75MM MIN. THICK SAND AND CEMENT SCREED (1:3) REINFORCED WITH FIBRE 500 GAUGE POLYTHENE VAPOR BARRIER ON 75MM CELOTEX FLOOR INSULATION WITH 25MM THICK VERTICAL INSULATION BOARD TO ALL EXPOSED PERIMETERS ON 1200 GAUGE POLYTHENE DPM ON 150-225MM (REFER TO SPECIALIST SUPPLIER DETAILS FOR FLOOR THICKNESS) THICK POTS AND BEAMS FLOORING SYSTEM. (FLOOR BLOCKS MUST HAVE THERMAL CONDUCTIVITY OF 0.15 (W/mk) OR BETTER). 150MM MINIMUM VENTED VOID. REFER TO FOUNDATIONS PLAN AND SECTIONS FOR FURTHER DETAILS. 2- GARAGE

SEE ENGINEER'S DESIGN

LINTELS. PRESSED STEEL LINTELS, MANUFACTURED FROM HOT DIP ZINC COATED PRESSED STEEL LINTELS, MANUFACTURED FROM HOT DIP ZINC COATED STEEL SHEET (IG, OR SIMILAR), TO BS 5977 PART 2, WITH ADDITIONAL INORGANIC FINISH AFTER FABRICATION WHERE APPLICABLE, AND FACTORY APPLIED INSULATION, LINTELS TO BE BUILT INTO POSITION, GENERALLY, WITH MINIMUM 150MM END BEARINGS, CAVITY TRAYS TO BE PROVIDED OVER LINTELS. CAVITY TRAY IS NOT REQUIRED OVER LINTELS UNDER ROOF EAVES. LINTELS TO BE DESIGNED BY MANUFACTURER'S DESIGN DEPARTMENT AND APPROVED BY PROJECT STRUCTURAL ENGINEER.

WINDOWS & DOORS WINDOWS AND DOORS TO BE WHITE UPVC. DOORS AND WINDOWS TO BE WEATHER-STRIPPED AND FRAMES TO BE FULLY SEALED INTERNALLY AND EXTERNALLY AGAINST MASONRY TO REDUCE AIR LEAKAGE. ALL WINDOWS AND DOOR FRAMES TO OVERLAP WALL CAVITY WITH 25MM MINIMUM. ALL WINDOWS TO HABITABLE ROOMS WITHOUT EXTERNAL DOOR TO BE EGRESS WINDOW WITH 450MM WIDE AND 750MM HIGH CLEAR OPENING, THE BOTTOM OF OPENING MUST BE BETWEEN 800-1100MM MAX. FROM FINISHED FLOOR LEVEL.

WINDOWS TO ACCOMMODATE 'TRICKLE VENTILATORS' TO PROVIDE 8000MM FOR HABITABLE ROOMS AND 4000MM ELSEWHERE. ALL HABITABLE ROOM TO HAVE OPENABLE AREA EQUAL TO 1/20TH FLOOR AREA.

ALL EXTERNAL GLAZING TO DOORS AND WINDOWS MUST BE DOUBLE GLAZED AND COMPRISING OF

4MM ANNEALED GLASS 24MM GAP WITH TPS SPACER AND FILLED WITH ARGON GAS. 4MM LOW 'E' SOFT COAT. (TO GIVE U VALUE OF 1.4 AND MANUFACTURER TO SUPPLY A CERTIFICATE).

SAFETY GLASS

GLASS WITHIN DOORS, SIDE PANELS TO DOORWAYS, PATIO/FRENCH CASEMENT DOORS, COMBINED DOOR AND WINDOW FRAME AND TO WINDOWS WITH LESS THAN 800MM FROM FINISHED FLOOR LEVEL IS TO BE SAFETY GLASS.

WHERE SAFETY GLASS IS SPECIFIED IT MUST COMPLY WITH THE REQUIREMENTS OF BS6206: 1981. SHOWER SCREENS TO BE SAFETY GLASS IF PROVIDED.

SECURED BY DESIGN STANDARD AND PART Q

ALL EXTERNAL WINDOWS AND DOORS (FRONT DOORS, SIDE DOORS, REAR DOORS, BI-FOLD DOORS, INTERCONNECTING GARAGE DOOR SET AND FRENCH CASEMENT DOORS) MUST CONFORM TO THE REQUIREMENTS OF SECURED BY DESIGN (2019 EDITION) AND PART Q. CONTRACTOR TO PRODUCE MANUFACTURER'S CERTIFICATES.

PITCHED ROOF.

ROOFING TILES (REFER TO COLOUR AND MATERIALS SCHEDULE FOR EACH PLOT) TO BE FIXED IN ACCORDANCE WITH MANUFACTURER'S REQUIREMENTS AND TO BS 5534 & 8000 WITH 100MM MINIMUM HEAD LAP FIX WITH COPPER NAILS TO BS 1202 PART 2, ON 50 X 25 IMPREGNATED BATTENS OVER ROOFING BREATHER MEMBRANE TO BS MPREGNATED BATTENS OVER ROOFING BREATHER MEMBRANE TO BS 5534 (TYVEK OR SIMILAR APPROVED) TO MANUFACTURERS REQUIREMENTS ON TRUSSED RAFTERS AT 600MM CENTRES (OR ENGINEER DESIGNED ROOF STRUCTURE). RAFTERS TO BE DESIGNED AND MANUFACTURED BY ROOF TRUSS SPECIALIST. DESIGN AND CALCULATIONS TO BE SUBMITTED TO BUILDING CONTROL AUTHORITY AND NHBC PRIOR TO COMMENCEMENT. FOR LONGITUDINAL AND DADONNAL DRACHNE REFER TO POOR TRUSSES MANUFACTURED FOR DIAGONAL BRACING REFER TO ROOF TRUSSES MANUFACTURER'S DESIGN. 100 X 50MM WALL PLATES TO BE FIXED TO INNER SKIN OF CAVITY WALL WITH 3 X 30 X 900MM LONG GALVANIZED STRAPS AT 1200MM CENTRES. STRAPS TO BE BENT AT 90 DEGREES TO GIVE 100MM BEARING ON TOP OF WALL PLATE. USE 4NO 3.5MM DIA. SCREWS AND PLUGS PER STRAPS. PROVIDE CONTINUOUS OVER FASCIA VENT (RYTONS OR SIMILAR) TO GIVE 10,000MM² FREE AIR PER METER RUN. SOFTWOOD DIAGONAL AND LONGITUDINAL BRACING AND METAL RESTRAINT STRAPS ALONG THE LINE OF CEILING JOISTS AND RAFTERS AT 1800MM MAXIMUM CENTRES, THE GALVANIZED METAL STRAPS ARE TO BE 30x5MM THICK AND LONG ENOUGH TO GIVE SECURE FIXING TO FIRST THREE TRUSSES WITH FULL DEPTH NUGGINGS, UNDER, STRAPS ARE TO BUILT INTO THE CAVITY WITH 150MM MINIMUM SECURED FIXING TO INNER SKIN IN ACCORDANCE WITH BS 5268: PART 3 AND NHBC REQUIREMENTS AND AS SHOWN ON THE TRUSSED MANUFACTURERS

DRAWINGS. CEILING TO BE LINED WITH 15MM THICK PLASTER BOARD AND SKIMMED. REFER TO SECTIONS FOR INSULATIONS AND LINING TO SLOPING CEILINGS AREAS.

ROOF TO BE INSULATED WITH THREE LAYERS OF 150MM THICK "ISOVER" INSULATION QUILT (450MM O/A). ONE LAYER BETWEEN CEILING JOISTS AND TWO LAYERS ACROSS AND OVER CEILING JOISTS PROVIDE 150MM THICK VERTICAL INSULATION OVER WALL PLATE TO TOP OF SOFFIT AS SHOWN ON SECTIONS. ROOF ACCESS HATCH TO BE FACTORY INSULATED WITH RUBBER SEALS

TO OPENING FRAME/TRAP.

FIRST FLOOR CONSTRUCTION

22MM THICK T&G MOISTURE RESISTANCE FLOORING GRADE BOARD ON ECOJOISTS (REFER TO MANUFACTURER'S FOR DESIGN, DETAILS AND INSTALLATION). ECOJOISTS TO BE BUILT INTO THE WALL, JOINTS AROUND JOISTS TO BE FULLY SEALED (REFER TO ROBUST DETAILS REQUIREMENT/CHECK LIST). FLOOR JOISTS DESIGN TO BE SUBMITTED TO BUILDING CONTROL AUTHORITY FOR APPROVAL. WHERE JOISTS ARE PARALLEL TO THE EXTERNAL WALLS, JOISTS TO BE TIED TO EXTERNAL CAVITY WALLS WITH 5MM THICK X 30MM WIDE X 1650MM LONG GALVANIZED METAL STRAPS (TO GIVE SECURE FIXING TO THE FIRST THREE JOISTS) AT MAXIMUM OF 2000MM CENTRES WITH FULL DEPTH SOLID BLOCKING UNDER STRAPS. STRAPS TO BE BENT AT 90 DEGREES AND BUILT INTO CAVITY TO GIVE 150MM MIN (REFER TO CARCASSING LAYOUT AND MANUFACTURER, DESIGN/DETAILS). PROVIDE 100MM MIN. THICK INSULATION QUILT BETWEEN JOISTS (ISOVER APR 1200). CEILING TO BE LINED WITH 15MM THICK BRITISH GYPSUM PLASTERBOARD AND TO BE TAPED AND SKIMMED.

ALL SPOT LIGHTS IN GROUND FLOOR CEILING TO HAVE APPROVED FIRE RATED HOODS.

AIR PERMEABILITY TEST

DWELLING TO BE AIR TESTED ON COMPLETION WITH AN APPROVED/REGISTERED AIR TESTING COMPANY TO THE CURRENT BUILDING REGULATIONS REQUIREMENTS. REFER TO SAP CALCULATIONS FOR EACH HOUSE TYPE FOR FURTHER DETAILS

HEATING.

AIR SOURCE HEAT PUMP BY SPECIALIST (REFER TO SUPPLIER DESIGN AND INSTALLATION SPECIFICATION AND REQUIREMENTS). HEATING SYSTEM MUST BE FITTED WITH APPROVED TIME AND TEMPERATURE ZONE CONTROL HOT WATER STORAGE TO BE FACTORY PRE PLUMBED "MEGAFLU". WITH CAPACITY BETWEEN 150–250 LTR. (REFER TO EACH HOUSE TYPE PLUMBING SCHEDULE FOR ACTUAL CAPACITY) ALL PIPES IN UNINSULATED SPACES SHALL BE INSULATED WITH ALL PIPES IN UNINSULATED SPACES SHALL BE INSULATED WITH INSULATION MATERIAL HAVING THERMAL CONDUCTIVITY OF 0.035 W/M.K AND A THICKNESS EQUAL TO OUTSIDE DIAMETER OF THE PIPE (40MM MAXIMUM). INSULATION TO EXTENAL PIPES TO BE IN ACCORDANCE WITI MANUFACTURER'S AND THE SYSTEM DESIGNER'S SPECIFICATION AND REQUIREMENTS. ZONE SYSTEM TO BE INSTALLED TO ALL HOUSE TYPES. REFER TO EACH HOUSE TYPE HEATING DESIGN FOR DESIGN DETAILS. GENERALLY GROUND FLOOR TO HEATED WITH UNDER FLOOR SYSTEM AN FIRST FLOOR WITH RADIATORES FIRST FLOOR WITH RADIATORES HEATING SYSTEM TO CONFORM TO CURRENT 'DOMESTIC HEATING COMPLIANCE GUIDE

MECHANICAL VENTILATION. MECHANICAL VENTILATION WILL BE PROVIDED AS FOLLOWS:-KITCHEN - COOKER HOOD AT 30 ITRE/SEC. BATHROOM & EN SUITS - EXTRACT FAN WITH 15 LITRE/SEC. UTILITY ROOM- EXTRACT FAN WITH 30 LITRE/SEC. WC- EXTRACT FAN TO GIVE 6 AIR CHANG PER/HOUR. WC WITHOUT WINDOW TO HAVE 15 MINUTES OVER-RUN AND CONNECTED TO THE LIGHT SWITCH

ELECTRICAL WORKS, ALL SOCKETS AND SWITCHES ARE TO BE INSTALLED BETWEEN 450MM AND 1200MM FROM FINISHED FLOOR LEVEL IN ACCORDANCE WITH PART "M" OF CURRENT BUILDING REGULATIONS.

ALL ELECTRICAL WORKS TO BE CARRIED OUT AND CERTIFIED BY A QUALIFIED MEMBER OF IEE OR OTHER APPROVED ORGANIZATIONS AS REQUIRED UNDER CURRENT BUILDING REGULATIONS PART "P" AND TO THE REQUIREMENTS OF BS 7671: 2001 AND IEE WIRING REGULATIONS 17th EDITION.

LOW ENERGY LIGHT FITTINGS, ALL LIGHTING POINTS ARE TO BE ENERGY SAVING LIGHT FITTINGS. EXTERNAL LIGHTS ARE TO BE ENERGY SAVING TYPE WITH SENSORS.

PART "L" REQUIREMENTS AND ACCREDITED CONSTRUCTION COMPLIANCE.

IN ORDER TO COMPLY TO THE REQUIREMENT OF PART "L" (ENERGY EFFICIENCY OF THE PROPERTY) THE PROJECT MUST BE BUILT TO THE ACCREDITED CONSTRUCTION DÉTAILS.

THE CONTRACTOR MUST KEEP THE RECORD OF COMPLIANCE AS REQUIRED BY THE ACT. FOR INFORMATION ON ACCREDITED CONSTRUCTION AND METHOD OF

COMPLIANCE AND RECORD KEEPING INCLUDING CONTRACTOR CERTIFICATION REFER TO "PLANNING PORTAL WEB SITE"

PART "G" REQUIREMENTS AND METHODS OF COMPLIANCE

WHOLESOME WATER CONSUMPTION ARE TO BE LIMITED TO 125 LITER PER PERSON PER DAY WHEN CALCULATED IN ACCORDANCE WITH A METROLOGY GIVEN IN DOCUMENT "WATER EFFICIENCY CALCULATOR FOR NEW DWELLINGS" THE MAIN CONTRACTOR AND PLUMBING CONTRACTOR TO ARE ENSURE THAT APPLIANCES AND FITTINGS ARE INSTALLED IN ACCORDANCE WITH THE CALCULATOR REQUIREMENTS.

WATER EFFICIENCY CALCULATION TO BE SUBMITTED TO L.A OR NHBC PRIOR TO COMPLETION.


AN AS-BUILT CHECKLIST OF ALL FITTINGS/APPLIANCES WITH THEIR FLOW RATES, SPECIFICATION AND MANUFACTURER DETAILS MUST BE GIVEN TO THE OWNER / OCCUPIERS OF THE PROPERTY.

HOT WATER OUTLET TEMPERATURE TO FIXED BATH TO BE LIMITED TO 48°C BY USE OF AN IN-LINE BLENDING VALVE OR OTHER APPROPRIATE TEMPERATURE CONTROL DEVICE. THE BLENDER/MIXER VALVE MUST BE LOCATED AS CLOSE AS POSSIBLE TO THE FINAL OUTLET.

AN ACCESS POINT (NETWORK PROVIDER'S ACCESS POINT) TO THE OUTSIDE DWELLING (NEAR FRONT DOOR) WITH SUITABLE DUCTING AND NETWORK TERMINATION POINTS WITHIN THE DWELLING TO BE PROVIDED. (IT IS RECOMMENDED THAT ONE PROVIDED FOR COMNECTION TO THE NETWORK. PROVIDED THAT ONE PROVIDED FOR CONNECTION TO THE NETWORK. PROVIDED THAT ONE THAT PERSON SINK: 40MM DIA. 75MM DEEP SEAL TRAP SINK: 40MM DIA. 75MM DEEP SEAL TRAP		PART "R"- PHYSICAL INFRASTRUCURE
TO THE OUTSIDE DWELLING (NEAR FRONT DOOR) WITH SUITABLE DUCTING AND NETWORK TERMINATION POINTS IN IS RECOMMENDED THAT ONE TERMINATION POINTS IN LOUNGE/KITCHEN DINNER TO BE PROVIDED FOR CONNECTION TO THE NETWORK. PLUMBING. WC: 100MM DIA. 75MM DEEP SEAL TRAP SHOWER: 40MM DIA. 75MM DEEP SEAL TRAP BASIN: 40MM DIA. 75MM DEEP SEAL TRAP BASIN: 40MM DIA. 75MM DEEP SEAL TRAP SHOWER: 40MM DIA. 75MM DEEP SEAL TRAP SINK: 40MM DIA. 4		FOR HIGH SPEED ELECTRONIC NETWORK, AN ACCESS POINT (NETWORK PROVIDER'S ACCESS POINT)
WITHIN THE DWELLING TO BE PROVIDED. (IT IS RECOMMENDED THAT ONE TERMINATION POINT IN EACH HABITABLE ROOM AND TWO POINTS IN LOUNGE/KITCHEN DINNER TO BE PROVIDED FOR CONNECTION TO THE NETWORK. PLUMBING. WIC: 100MM DIA. 75MM DEEP SEAL TRAP BASH: 40MM DIA. 75MM DEEP SEAL TRAP BASH: 40MM DIA. 75MM DEEP SEAL TRAP BASH: 40MM DIA. 75MM DEEP SEAL TRAP SHOWER: 40MM DIA. 75MM DEEP SEAL TRAP SHOWER: 40MM DIA. 75MM DEEP SEAL TRAP SHOWER: 40MM DIA. 75MM DEEP SEAL TRAP SIN: 40MHERE TWO OR DECRESS TO BE PROVIDED WHERE TWO OR MORE ARE FITTED TO BE LINKED. (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. (TO BS 5446-2 IS 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. (BALLSTREE TWO OR MORE ARE FITTED TO BE LINKED.	_	TO THE OUTSIDE DWELLING (NEAR FRONT DOOR) WITH
CACH HABITABLE ROOM AND TWO POINTS IN LOUNCEX(HITCHEN DINNER TO BE PROVIDED FOR CONNECTION TO THE NETWORK. PLUMBING. WC: 100MM DIA. 75MM DEEP SEAL TRAP BAOWER: 40MM DIA. 75MM DEEP SEAL TRAP BATH: 40MM DIA. 75MM DEEP SEAL TRAP BATH: 40MM DIA. 75MM DEEP SEAL TRAP SINK: 40MM DIA. 75MM DEEP SEAL TRAP SINC. SUPCIDE SINCE SINCE SINCE SINCE COVER FOR CLEANING ACCESS TO BE PROVIDED.WHERE WASTE PIPE FROM ANY APPLIANCES CHANGES DIRECTION BEFORE COVER FOR CLEANING ACCESS TO BE PROVIDED.WHERE WASTE PIPE FROM ANY APPLIANCES CHANGES DIRECTION BEFORE COVER FOR CLEANING ACCESS TO BE PROVIDED.WHERE WASTE PIPE FROM ANY APPLIANCES CHANGES DIRECTION BEFORE COVER FOR CLEANING ACCESS TO BE PROVIDED.WHERE WASTE PIPE FROM ANY APPLIANCES CHANGES DIRECTION BEFORE COMMINICUM MILEAP ROOM. REFER TO TO THE SVP. SIMMONG ONG 42 DEGRRES MAX. PITCH RALLING TO BE 900MM HIGH. WITH BALUSTRADES AT 100MM CENTRES 200MM MINIMUM MEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS SIMMONG DECOMENTIONER (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 MT OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 MT OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 MT OF ANY HABITABLE ROOM, AND TO BE LOCA	کر	WITHIN THE DWELLING TO BE PROVIDED.
CONNECTION TO THE NETWORK. PLUMBING. WC: 100MM DIA. 75MM DEEP SEAL TRAP BASIN: 40MM DIA. 75MM DEEP SEAL TRAP BASIN: 40MM DIA. 75MM DEEP SEAL TRAP SIN: 40MM DIA. 75MM DEEP SEAL TRAP SOUTH THE SIN: 40MM CEANTRON 200MM MINI GOING 42 DEGRRES MAX. PITCH RAILING TO E 90MM HIGH. WITH BALUSTRADES AT 100MM CENTRES 200MM MININUM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING C HANDIRE FLAND SOFRATED ON THE NEULTION STAGE. D HEATING SERST FLOOR NOTES (12 HARDIE FLANG BERNING OMTED B NEULTION STAGE. D HEATING SERST FLOOR NOTES (20 HARDIE FLANG BERNING OMTED B NEULTION STAGE. D HEATING SERST CORMUNAS ADD FLEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE.	<	
PLUMBING. WC: 100MM DIA. 75MM DEEP SEAL TRAP SHOWER: 40MM DIA. 75MM DEEP SEAL TRAP BASIN: 40MM DIA. 75MM DEEP SEAL TRAP BASIN: 40MM DIA. 75MM DEEP SEAL TRAP SINK: 40MM DIA. 75MM DEEP SEAL TRAP SOM DEA REFER TO STAIRCASE SUPPLIER'S DETAILS 13 EQUAL RISERS (2675MM TOTAL RISE APPROX.) AND TO BE CHECK ON SITE PRIOR 10 FABRCATION. 230MM MIN. GOING 42 DEGRES MAX. PITCH RALING TO BE 900MM HIGH. WITH BALUNG TO BE 900MM HIGH. WITH BALUNG TO BE 900MM HIGH. WITH BALUNG TO SAGERES WAX. PITCH RALING TO SAGEACHERS WAX. PITCH RALING TO SAGEACHERS WAX. PITCH RALING TO SAGEACHERS WAX. PITCH	<	
WC: 100MM DIA. 75MM DEEP SEAL TRAP SHOWER: 40MM DIA. 75MM DEEP SEAL TRAP BASIN: 40MM DIA. 75MM DEEP SEAL TRAP BASIN: 40MM DIA. 75MM DEEP SEAL TRAP SINK: 40MM DIA. 75MM DEEP SEAL TRAP SOMM DIA. AND TO BE TERMINATED 900MM MINIMUM ABOVE ANY WINDOW 0PENING. WHERE LENGTH OF WASTE PIPE EXCEED 3M FROM THE SVP, IT MUST BE INCREASES TO SOMM DIA. SHOWER TRAP MUST HAVE ACCESSIBLE COVER FOR CLEANING. COUVER TRAP MUST HAVE ACCESS TO BE PROVIDED WHERE WASTE PIPE FROM ANY APPROX.) AND TO BE CHECK ON SITE PRIOR 0 COVER TRAP MUST HAVE ACCESS TO BE PROVIDED WHERE WASTE COTCH RAILING TO BE 900MM HIGH. WITH BALUSTRADES AT 100MM CENTRES 2000M MINIM MIM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS 30 MOKEE & HEAT DETECTORS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE	<	
BATH: 40MM DIA. 75MM DEEP SEAL TRAP BATH: 40MM DIA. 75MM DEEP SEAL TRAP SINK: 40MM DIA. 75MM DEEP SEAL TRAP SINK: 40MM DIA. AND TO BE TERMINATED 900MM MINIMUM ABOVE ANY WINDOW OPENING. WHERE LENGTH OF WASTE PIPE EXCEED 3M FROM THE SVP, IT MUST BE INCREASES TO 50MM DIA. SHOWER TRAP MUST HAVE ACCESSIBLE COVER FOR CLEANING. RODDING /CLEANING ACCESS TO BE PROVIDED, WHERE WASTE PIPE FROM ANY APPLIANCES CHANNES DIFECTION BEFORE CONNECTING TO THE SVP. STAIRCASES REFER TO STAIRCASE SUPPLIER'S DETAILS 13 EQUAL RISERS (2675MM TOTAL RISE APPROX.) AND TO BE CHECK ON SITE PRIOR TO FABRICATION. 230MM MIN. GOING 42 DEORRES MAX. PITCH RALING TO BE 900MM HIGH. WITH BALUSTRADES AT 100MM CENTRES 2000MM MINIMUM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON TŁOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY APPROVED QUALIFIED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING A FIRST FLOOR NOTES 07/21 REVENENCE AND REGISCOMMENTS ADDED BUINTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING A FIRST FLOOR NOTES 07/21 REVENENCE	<	WC: 100MM DIA. 75MM DEEP SEAL TRAP
 SVP:100MM DIA. AND TO BE TERMINATED 900MM MINIMUM ABOVE ANY WINDOW 900KM MINIMUM ABOVE ANY WINDOW 900KM TRAP MUST HAVE ACCESSIBLE COVER FOR CLEANING. SHOWER TRAP MUST HAVE ACCESSIBLE COVER FOR CLEANING ACCESS TO BE PROVIDED, WHERE WASTE PIPE FROM ANY APPPLIANCES CHANCES DIRECTION BEFORE CONNECTING TO THE SVP. STAIRCASES REFER TO STAIRCASE SUPPLIER'S DETAILS 13 EQUAL RISERS (2675MM TOTAL RISE APPROX). AND TO BE CHECK ON SITE PRIOR TO FABRICATION. 230MM MIN. GOING 42 DEGRRES MAX. PITCH RALING TO BE 900M HIGH. WITH BALUSTRADES AT 100MM CENTRES 2000MM MINIMUM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS S 40 SMOKE & HEAT DETECTORS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. 	<	BASIN: 40MM DIA. 75MM DEEP SEAL TRAP
900MM MINIMUM ABOVE ANY WINDOW 0PERING. WHERE LENGTH OF WASTE PIPE EXCEED 3M PROW THE SVP, IT MUST BE INCREASES TO 50MM DIA. SHOWER TRAP MUST HAVE ACCESSIBLE COVER FOR CLEANING. RODDING /CLEANING ACCESS TO BE PROVIDED, WHERE WASTE PIPE FROM ANY APPLIANCES CHANCES DIRECTION BEFORE CONNECTING TO THE SVP. STAIRCASES REFER TO STAIRCASE SUPPLIER'S DETAILS 13 EQUAL RISERS (2675MM TOTAL RISE APPROX.) AND TO BE CHECK ON SITE PRIOR 0 FARICATION. 230MM MIN. GOING 42 DEORRES MAX. PITCH RALING TO BE 900MM HIGH. WITH BALUSTRADES AT 100MM CENTRES 2000MM MINIMUM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF A	<	SINK: 40MM DIA. 75MM DEEP SEAL TRAP
WHERE LENGTH OF WASTE PIPE EXCEED 3M FROM THE SVP, IT MUST BE INCREASES TO 50MM DIA. SHOWER TRAP MUST HAVE ACCESSIBLE COVER FOR CLEANING. RODDING /CLEANING ACCESS TO BE PROVIDED/WHERE WASTE PIPE FROM ANY APPLIANCES CHANGES DIPECTION BEFORE CONNECTING TO THE SVP. TAIRCASE REFER TO STAIRCASE SUPPLIER'S DETAILS 13 EQUAL RISERS (2675MM TOTAL RISE APPROX.) AND TO BE CHECK ON SITE PRIOR TO FABRICATION. 230MM MIN. GOING 42 DEGRRES MAX. PITCH RAILING TO BE 900MM HIGH. WITH BALUSTRADES AT 100MM CENTRES 2000MM MINIMUM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING A FIRST FLOOR NOTES 09/21 REVISED A BUILDING REGS.COMMENTS ADDED B NOSULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING A FIRST FLOOR NOTES 09/21 REVISED A BUILDING REGS.COMMENTS ADDED B NOSUR AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING A FIRST FLOOR NOTES 09/21 C HARDIE PLANK BOARDING OMITTED B NOSURATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING A FIRST FLOOR NOTES D HORDIE PLANK BOARDING OMITTED D HORDIE PLANK BOARDING OM	+ <	900MM MINIMUM ABOVE ANY WINDOW
Solver trap must have accessible Cover for cleaning. Rodding Collaming access to be Provided where waste pipe from any Appliances changes direction before connecting to the svp. Staincases Refer to Staircase supplier's details 13 Equal Risers (2675MM total Rise Approx.) and to be check on site prior to Fabrication. 230MM MiN. Going 42 Degrees Max. Pitch Ralling to be 900MM High, with Balustrades at 100MM centres 2000MM Minimum Head Room. Refer to House type Drawings for Further Details (To Bs 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) To Be Mains OPERATED with Battery Back UP AND WHERE Two or More Are fitted to Be Linked. Heat Detector to Be Installed in kitchen As Shown on the Layout And Smoke Alarms to Be Installed In Hall AND LANDING TO WITHIN 3 Mtr of Any Habitable Room, And to Be Located As Shown on Floor Plans. All Electrical Works to Certificed By Approved Qualified Person/Firm As Required By Building Regulations AND Relevant Certificates to Be Submitted To the Building control At C Hardie Plank Bartery Back up All Electrical Works to Certificates to Be Submitted To the Building control At Completion Stage. D Heating arist floor notes 09/21 Revised A Building regs.comments and By Noge, Moor Road, Langham Colchester, Essex, Cod 5NR	<	WHERE LENGTH OF WASTE PIPE EXCEED 3M
COVER FOR CLEANING. RODDING / CLEANING ACCESS TO BE PROVIDED,WHERE WASTE PIPE FROM ANY APPLIANCES CHANGES DIRECTION BEFORE CONNECTING TO THE SVP. STAIRCASES REFER TO STAIRCASE SUPPLIER'S DETAILS 13 EQUAL RISERS (2675MM TOTAL RISE APPROX.) AND TO BE CHECK ON SITE PRIOR TO FABRICATION. 230MM MIN. GOING 42 DEGRRES MAX. PITCH RAILING TO BE 900MM HIGH. WITH BALUSTRADES AT 100MM CENTRES 2000MM MINIMUM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS SOLO SMOKE & HEAT DETECTORS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING AFIRST FLOOR NOTES <i>MUSCONDERSES.COMMENTS AND REVISED</i> A BUILDING REGS.COMMENTS AND <i>MUSCONTROL AT COMPLETION STAGE.</i> D HEATING A FROMENTS ADDED <i>MUSCOND CONTROL AT</i> <i>COMPLETION STAGE.</i>	D <	
RODDING / CLEANING ACCESS TO BE PROVIDED, WHERE WASTE PIPE FROM ANY APPLIANCES CHANGES DIRECTION BEFORE CONNECTING TO THE SVP. STAIRCASES REFER TO STAIRCASE SUPPLIER'S DETAILS 13 EQUAL RISERS (2675MM TOTAL RISE APPROX.) AND TO BE CHECK ON SITE PRIOR TO FABRICATION. 230MM MIN, GOING 42 DEGRRES MAX. PITCH RAILING TO BE 900MM HIGH. WITH BALUSTRADES AT 100MM CENTRES 2000MM MINIMUM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS ③ ④ SMOKE & HEAT DETECTORS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE	<	
APPLIANCE'S CHANGES DIRECTION BEFORE CONNECTING TO THE SVP. STAIRCASES REFER TO STAIRCASE SUPPLIER'S DETAILS 13 EQUAL RISERS (2675MM TOTAL RISE APPROX.) AND TO BE CHECK ON SITE PRIOR TO FABRICATION. 230MM MIN. GOING 42 DEGRRES MAX. PITCH RAILING TO BE 900MM HIGH. WITH BALUSTRADES AT 100MM CENTRES 2000MM MINIMUM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS SMOKE & HEAT DETECTORS (TO BS 5446-2: 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D MEATING & FIRST FLOOR NOTES B INSTALLED IN THE BUILDING CONTROL AT COMPLETION STAGE. D MEATING & FIRST FLOOR NOTES A BUILDING REGS.COMMENTS ADDED D MEATING & FIRST FLOOR NOTED D ME	Ĵ	RODDING /CLEANING ACCESS TO BE
STAIRCASES REFER TO STAIRCASE SUPPLIER'S DETAILS 13 EQUAL RISERS (2675MM TOTAL RISE APPROX.) AND TO BE CHECK ON SITE PRIOR TO FABRICATION. 230MM MIN. GOING 42 DEGRRES MAX. PITCH RAILING TO BE 900MM HIGH. WITH BALUSTRADES AT 100MM CENTRES 2000MM MINIMUM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS O O SMOKE & HEAT DETECTORS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING AFIRST FLOOR WILLS AND REFERSION. D HEATING AFIRST FLOOR WILLS AND D HEATING AFIRST FLOOR MORTED D HEATING AFIRST FLOOR WILLS AND D HEATING AFIRST F		APPLIANCES CHANGES DIRECTION BEFORE
REFER TO STAIRCASE SUPPLIER'S DETAILS 13 EQUAL RISERS (2675MM TOTAL RISE APPROX.) AND TO BE CHECK ON SITE PRIOR TO FABRICATION. 230MM MIN. GOING 42 DEGRRES MAX. PITCH RAILING TO BE 900MM HIGH. WITH BALUSTRADES AT 100MM CENTRES 2000MM MINIMUM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES 09/21 C HARDIE PLANK BOARDING OMITTED A DUILDING REGS. COMMENTS ADDED 0/21 AREVISED A DUILDING REGS. COMMENTS ADDED ACREVISED A REVISED A REVISED A DUILDING REGS. COMMENTS ADDED D HEATING & FIRST FLOOR NOTES 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21		
APPROX.) AND TO BE CHECK ON SITE PRIOR TO FABRICATION. 2300M MIN. GOING 42 DEGRRES MAX. PITCH RAILING TO BE 900MM HIGH. WITH BALUSTRADES AT 100MM CENTRES 2000MM MINIMUM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES 09/21 REVISED A BUILDING REGS. COMMENTS ADDED 0/27 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/21 0/2		REFER TO STAIRCASE SUPPLIER'S DETAILS
230MM MIN. GOING 42 DEGRRES MAX. PITCH RAILING TO BE 900MM HIGH. WITH BALUSTRADES AT 100MM CENTRES 2000MM MINIMUM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES 09/21 REVISED A BUILDING REGS.COMMENTS ADDED 06/21 D HEATING & FIRST FLOOR NOTES 09/21 C HARDIE PLANK BOARDING OMITTED B INSULATIONS TO FLOOR, WALLS AND ROUPLETION STAGE.		
42 DEGRRES MAX. PITCH RAILING TO BE 900MM HIGH. WITH BALUSTRADES AT 100MM CENTRES 2000MM MINIMUM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES 09/21 REVISED C HARDIE PLANK BOARDING OMITTED B INSULATIONS TO FLOOR, WALLS AND ROOF REVISED A BUILDING REGS. COMMENTS ADDED (0/21 REV DESCRIPTION ARCHICCUTAL & PROPERTY CONSULTANTS D HEATING & FIRST FLOOR NOTES 09/21 D HEATING		
BALUSTRADES AT 100MM CENTRES 2000MM MINIMUM HEAD ROOM. REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS		42 DEGRRES MAX. PITCH
REFER TO HOUSE TYPE DRAWINGS FOR FURTHER DETAILS S A SMOKE & HEAT DETECTORS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES 09/21 REVISED C HARDIE PLANK BOARDING OMITTED B INSULATIONS TO FLOOR, WALLS AND ROOF REVISED A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 SNR		BALUSTRADES AT 100MM CENTRES
 SMOKE & HEAT DETECTORS (TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 1404:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. MENDARING AFIRST FLOOR NOTES 09/21 REVISED HEATING & FIRST FLOOR NOTES 09/21 REVISED BUILDING REGS. COMMENTS ADDED ROF REVISED BUILDING REGS. COMMENTS ADDED REVISED A BUILDING REGS. COMMENTS ADDED REVISED 		REFER TO HOUSE TYPE DRAWINGS FOR
(TO BS 5446-2 : 2003, BS 5839-6: 2004 (GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES B INSULATIONS TO FLOOR, WALLS AND ROOF REVISED A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED Architectural & Property Consultants Hyridge, MoOR KOAL, Langham Colchester, Essex, CO4 5NR		
(GRADE D2-CATEGORY LD3) AND BS EN 14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES NOOF REVISED 09/21 08/21 07/21 08/21 06/21 07/21 REVISED D HEATING & FIRST FLOOR NOTES NOOP LEVISED 09/21 08/21 07/21 08/21 07/21 08/21 06/21 Date		S ⊕ SMOKE & HEAT DETECTORS
14604:2005) TO BE MAINS OPERATED WITH BATTERY BACK UP AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES NOPLETION STAGE. D HEATING & FIRST FLOOR NOTES A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED A CONTROL AT CORPLETION STAGE. D HEATING & FIRST FLOOR NOTES A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED A CONTROL AT CORPLETION STAGE. D HEATING & FIRST FLOOR NOTES A BUILDING REGS. COMMENTS ADDED A CONTROL AT CORPLETION A BUILDING REGS. COMMENTS ADDED A CONTROL AT CORPLETION A CONTROL AT CORPLETION A BUILDING REGS. COMMENTS ADDED A CONTROL AT CORPLETION A BUILDING REGS. COMMENTS ADDED A CONTROL AT A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED A CONTROL AT A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED A CONTROL AT A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED A CONTROL AT A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. C		
AND WHERE TWO OR MORE ARE FITTED TO BE LINKED. HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES 09/21 REVISED C HARDIE PLANK BOARDING OMITTED B INSULATIONS TO FLOOR, WALLS AND ROOF REVISED A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 SNR		14604:2005)
HEAT DETECTOR TO BE INSTALLED IN KITCHEN AS SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES REVISED C HARDIE PLANK BOARDING OMITTED B INSULATIONS TO FLOOR, WALLS AND ROOF REVISED A BUILDING REGS. COMMENTS ADDED Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR		
SHOWN ON THE LAYOUT AND SMOKE ALARMS TO BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES 09/21 REVISED C HARDIE PLANK BOARDING OMITTED B INSULATIONS TO FLOOR, WALLS AND ROOF REVISED A BUILDING REGS. COMMENTS ADDED 06/21 Rev Description Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 SNR		LINKED.
Mtr OF ANY HABITABLE ROOM, AND TO BE LOCATED AS SHOWN ON FLOOR PLANS. ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES C HARDIE PLANK BOARDING OMITTED B INSULATIONS TO FLOOR, WALLS AND ROOF REVISED A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR		
ALL ELECTRICAL WORKS TO CERTIFIED BY APPROVED QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES 09/21 REVISED C HARDIE PLANK BOARDING OMITTED B INSULATIONS TO FLOOR, WALLS AND ROOF REVISED A BUILDING REGS. COMMENTS ADDED A BUILDING REGS. COMMENTS ADDED Date CHILDING REGS. COMMENTS ADDED Date A BUILDING REGS. COMMENTS ADDED Date CHILDING REGS. COMMENTS ADDED COLCHESTER, MOOR ROAD, Langham COLCHESTER, ESSEX, CO4 SNR		BE INSTALLED IN HALL AND LANDING TO WITHIN 3 Mtr of any habitable room, and to be located
QUALIFIED PERSON/FIRM AS REQUIRED BY BUILDING REGULATIONS AND RELEVANT CERTIFICATES TO BE SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES 09/21 REVISED C HARDIE PLANK BOARDING OMITTED B INSULATIONS TO FLOOR, WALLS AND ROOF REVISED A BUILDING REGS. COMMENTS ADDED 06/21 Rev Description Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR		AS SHOWN ON FLOOR PLANS.
SUBMITTED TO THE BUILDING CONTROL AT COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES 09/21 REVISED C HARDIE PLANK BOARDING OMITTED B INSULATIONS TO FLOOR, WALLS AND ROOF REVISED A BUILDING REGS. COMMENTS ADDED Rev Description Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR		
COMPLETION STAGE. D HEATING & FIRST FLOOR NOTES 09/21 REVISED C HARDIE PLANK BOARDING OMITTED 08/21 B INSULATIONS TO FLOOR, WALLS AND ROOF REVISED 07/21 A BUILDING REGS. COMMENTS ADDED 06/21 Rev Description Date		
C HARDIE PLANK BOARDING OMITTED 08/21 B INSULATIONS TO FLOOR, WALLS AND 07/21 ROOF REVISED A BUILDING REGS. COMMENTS ADDED 06/21 Rev Description 04/21 04/21 HARDE PLANK BOARDING OMITTED 06/21 06/21 Rev Description 06/21 Description Date 06/21 Colchester, Essex, CO4 5NR Colchester, Essex, CO4 5NR		
C HARDIE PLANK BOARDING OMITTED 08/21 B INSULATIONS TO FLOOR, WALLS AND 07/21 ROOF REVISED A BUILDING REGS. COMMENTS ADDED 06/21 Rev Description 04/21 04/21 HADD HOMMENTS ADDED 06/21 04/21 Rev Description 04/21 04/21 B HULDING REGS. COMMENTS ADDED 06/21 04/21 Description Date 04/21 04/21 Colchester, Essex, CO4 Colchester, Essex, CO4 SNR		
B INSULATIONS TO FLOOR, WALLS AND ROOF REVISED A BUILDING REGS. COMMENTS ADDED Rev Description Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR		REVISED
A Rev Description 06/21 Description 06/21 Description 06/21 Detervious 06/21 De		B INSULATIONS TO FLOOR, WALLS AND 07/21
HD Homa Design Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR		A BUILDING REGS. COMMENTS ADDED 06/21
Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR		Rev Description Date
Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR		HD Homa Design
Colchester, Essex, CO4 5NR		Architectural & Property Consultants
Email: homa@homadesign.co.uk		


Client --Project LANSWOOD PARK ELMSTEAD COLCHESTER CO7 7FD GENERAL CONSTRUCTION SPECIFICATION

Date NOV 2020 Scale: N/A Drawing No. CON-SPEC-01 ppyright 🔘 Homa Design L



FOUNDATIONS, FLOOR SLAB, SERVICE ENTRY LAYOUT (HOUSE TYPES T6 & T6A) THIS DRAWING TO BE READ IN CONJUNCTION WITH ENGINEER, PC FLOOR MANUFACTURER, SERVICES SUPPLIERS DRAWINGS AND SPECIFICATION

A INTERNAL PARTITION REVISED APR 21 Date HD Homa Design Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR Tel: 01206 272247 Email: homa@homadesign.co.uk Client --Project LANSWOOD PARK ELMSTEAD COLCHESTER CO7 7FD Drawing HOUSE TYPES T6 & T6A GENERAL ARRANGEMENT FOUNDATIONS PLAN Date NOV 2020 Scale: 1:50 @ A3 Drawing No. T6-01-01 Copyright 🔘 Homa Design



75MM SAND AND CEMENT SCREED WITH D49 MESH

500 GAUGE VAPOR BARRIER

75MM CELOTEX OR XTRATHERM

1200 GAUGE DPM

150MM PC FLOOR

 Rev Description	n		 Date
Architectt Hyridge, N Colchester Tel: 01200 Email: hor	DE Moor H r, Esse 5 2722	Property Consultan Road, Langham x, CO4 5NR 47 omadesign.co.uk	T11 nts
Client			
Project			
LANSWC	-	PARK	
ELMSTE	AD		
COLCHE	STE	R CO7 7FD	
1	TION	TION THROU IS AND EXTEI OOR	
SHEET 8			
Date NOV 2	020	Scale: 1:20 @ A3	
Drawing No.	DET-	01-09	-
Copyright C Ho	ma Des	ign Ltd Do i	not scale

		DOOR SCHEDULE	
REF. NO.	DOOR LEAF SIZE W x H (mm)	NOMINAL FRAME / LINING SIZE W x H (mm)	STRUCTURAL OPENING
D1*	*	990 x 2090	1000 x 2100
D2	826 x 2040	890 x 2072	910 x 2100
D3	826 x 2040	890 x 2072	910 x 2100
D4	726 x 2040 pair	1516 x 2072	1536 x 2100
D5	726 x 2040	790 x 2072	810 x 2100
D6*	*	2590 X 2165	2600 X 2175
D7*	*	890 x 2090	900 x 2100
D8	726 x 2040	790 x 2072	810 x 2100
D9	726 x 2040	790 x 2072	810 x 2100
D10	726 x 2040	790 x 2072	810 x 2100
D11	726 x 2040	790 x 2072	810 x 2100
D12	726 x 2040	790 x 2072	810 x 2100
D13	726 x 2040	790 x 2072	810 x 2100
D14	726 x 2040	790 x 2072	810 x 2100
D15	726 x 2040	790 x 2072	810 x 2100
D16	626 x 2040	690 x 2072	710 x 2100
	WINDOW	S AND LINTEL SCHEDUI	Ē
REF.			MARKS
<u>NO.</u> W01	W x H (n 1800 x 1500		
W02	600 x 1350	,	
W02	1800 x 1050		
W03	600 x 1200)	
W04	1200 x 1200		
W05	1200 x 1200		
W08	600 x 1050	,	
W07	1800 x 1050)	
W08	600 x 1050	,	
W10	600 x 1000		
vv 10			

REMARKS:


FD20 - 20 MINUTES FIRE DOOR AND FRAME TO CURRENT BUILDING REGULATIONS.

- ★ SIZE OF DOOR LEAF INCLUDING STYLES ARE TO BE AGREED AND CONFIRMED. LEVELED THRESHOLD TO PART "M" REQUIREMENT.
- $\bigstar\bigstar$ ANY GLAZING IN ANY DOOR TO BE TOUGHENED SAFETY GLASS.


SECURED BY DESIGN STANDARD

ALL EXTERNAL WINDOWS AND DOORS (FRONT DOORS, SIDE DOORS, REAR DOORS, BI-FOLD DOORS, INTERCONNECTING GARAGE DOOR SET AND FRENCH CASEMENT DOORS) MUST CONFORM TO THE REQUIREMENTS OF SECURED BY DESIGN (2019 EDITION). CONTRACTOR TO PRODUCE MANUFACTURER'S CERTIFICATES.

PROVIDE 63 X 44MM SOFTWOOD STUD AROUND ALL INTERNAL DOOR FRAMES (SIDES AND HEAD)




11/05/2022 12:12:02




A FIRST ISSUE Rev Description APR 21 Date HD Homa Design Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR Tel: 01206 272247 Email: homa@homadesian.co.uk Email: homa@homadesign.co.uk Client --Project LANSWOOD PARK ELMSTEAD COLCHESTER CO7 7FD Drawing HOUSE TYPE 6 (T6) GENERAL ARRANGEMENT FIRST FLOOR PLAN Date NOV 2020 Scale: 1:50 @ A3 Drawing No. T6-02-02 A Copyright 🛈 Homa Design Ltd not scale







1:50



FIRST FLOOR PLAN 1:50

STRUCTURAL STEELWORK NOTES

- 1. All materials, fabrication, workmanship and erection of steelwork shall be in accordance with the National Steelwork Specification for Building Construction, 5th edition as published by the British Constructional Steelwork Association.
- 2. Steelwork connections shall comprise not less than: 2No. M16 dia. gr. 8.8 bolts for members up to 25 kg/m 4No. M16 dia. gr. 8.8 bolts for all other members, except where otherwise shown on the drawings. All bolts to BS 3692.
- Where connection loads are provided by the Engineer, the steelwork contractor shall design connections which will be subject to comment by the Engineer.
- 3. Where packers are used in connections, the maximum thickness of packers is not to exceed 4 x bolt Ø / 3. For multiple plies of packer, no more than 4 plies should be used.
- 4. All connections to be designed for a minimum load of 25kN in Shear and 75kN in Tension.
- 5. All butt welds are to be properly prepared and to be full strength and 4. penetration. All fillet welds to be min. 6mm full profile U.N.O. All welds to be tested in accordance with BS EN 288.
- 6. Steel beams shall at least have the minimum bearings on masonry 5. walls as shown on the drawings. Where no details of bearings are shown provide bearings to the full width of the supporting leaf or 150mm whichever is greater.
- 7. Steel columns shall be raised or lowered to the correct levels off foundations/masonry supports using sawn steel packs not less than 75mm square. Allowance shall be made for nominal 25mm thickness of grout between column baseplates and foundations/masonry supports. Grout shall take the form of neat cement slurry with a nonshrink additive and should be just fluid enough to pour.
- 8. Site modifications to structural steelwork shall not be carried out unless prior approval has been obtained from the Engineer.
- 9. All structural steelwork shall be blast cleaned to BS EN ISO 8501-1, preparation grade SA 2 1/2 and, except where specified as galvanised, shall be painted with a suitable good quality high build epoxy zinc phosphate primer to provide a dry film thickness of not less than 80 microns. A pre-fabrication primer may be used at the fabricators discretion. The contractor shall ensure that the primer used is compatible with subsequent coatings specified by others. (e.g. Intumescent paint).
- 10. Steelwork specified as galvanised shall be blast cleaned as above & hot dip galvanised to BS EN ISO 1461 minimum coating thickness 85 microns. Corrosion category to be C3 BS EN ISO 12944-2.
- 11. All steelwork below DPC level or built within the masonry wall cavity shall additionally be site painted with a compatible high build epoxy 8. Lintels zinc phosphate primer to provide a dry film thickness of not less than 120 microns, to achieve an overall primer coating of 200 microns. i.e. LEIGHS PAINTS EPIGRIP C400 zinc phosphate primer/buildcoat or equal.
- 12. Steelwork below DPC and adjacent to soil shall be encased in concrete with cover of not less than 100mm. A reduced cover of 50mm will be permitted when cast against masonry or additional protection is provided. Concrete to be not weaker than C20/25 N/mm2 at 28 days to BS EN 206-1, BS 8500-1 and BS 8500-2.
- 13. The Engineer is not responsible for dimensional information except where shown on his drawings. All setting out information, dimensions etc. shall be obtained from the architects drawings. All Steelwork levels, even those shown on the Engineers drawings must be confirmed or obtained from the Architects drawings.
- 14. The Steelwork Contractor is to co-ordinate with the Main Contractor and cladding Contractor to provide all necessary secondary steelwork, trimming etc. as required around all doors, windows and the like.
- 15. Steelwork Contractor to co-ordinate with the Main Contractor to provide adequate temporary bracing and propping during the sequence of erection.
- 16. Unless prior written approval is given by the Structural Engineer, the steelwork shall not be used for any temporary lifting or as part of a fall arrest system.
- 17. All Steelwork is to be fire protected to the Architects details but with a minimum that all Internal Steelwork to be clad with 2 layers of 12.5mm plasterboard, with 16 gauge wire bindings at 100mm centres and plaster skimmed to a minimum thickness of 5mm.
- 18. All holes to be drilled not punched.
- 19. The Execution and Consequence Class for the structure is EXC2/CC1 to BS EN 1090-2. All fabricated structural steelwork shall be CE marked in accordance with BS EN 1090-1.
- 20. Unless specified otherwise, Grade S355 steelwork shall be used throughout. Where RHS, SHS or CHS members are specified, use Grade S355NH steelwork to BS EN 10025 (U.N.O.).

<u>KEY</u>

- Indicates Span direction of propietary engineered timber joist system.
- Denotes span direction of standard timbre trussed rafters at maximum 600mm centres, designed and manufactured by specialist trussed rafter manufacturer.
- Ancon WP3 windpost or similar approved. WP
- Denotes location of Trimmer Beams, ΤВ designed by specialist supplier.

Denotes bracing walls - Allow 3kN/m SLS load on the floor. Bracing walls to comprise minimum 72mm studwork at 600mm centres max, with 9mm OSB3 lining to one side fixed to studs using 3.25mm Nails at 150mm centres max. 'Sole plate' to be fixed to the floor with 90x90 angle brackets at 1500mm max centres. 'End stud' to be fixed to inner leaf @ 225 centres internally.

Key	Description	1
	3.6 N/mm ² Blocks	
	7.3 N/mm ² Blocks	
	10.4 N/mm ² Blocks	
	17.5 N/mm ² Blocks	
	22.5 N/mm ² Blocks	
	Denotes bracing walls	
floor. Brac at 600mm	g Walls allow 3kN/m SLS load on the ing walls to comprise min. 72mm studs centres max, with 9mm OSB3 lining to xed to studs using 3.25mm Nails at	-

STRUCTURAL MASONRY NOTES

2.

Blockwork to have a minimum compressive strength as specified on the drawings. All blockwork to be solid unless specified otherwise on the drawings and is to comply with BS5628, Table 4, requirements for CATEGORY 1 of manufacture in accordance with BS EN 771-1 to 6. The maximum weight of an individual masonry unit must not exceed 20kg. Blockwork should be adequately protected on site to avoid saturation and possible increase in lifting weight. Reference shall be made to the Project Architect/Acoustic Consultant for compliance with Part E of the Building Regulation - Sound Transmission.

Blockwork below DPC to be of foundation quality (refer to Manufacturers guidelines) and to be of at least equal minimum compressive strength to that indicated between ground and first floor and in no case less than 7.3N/mm².

Movement joints. Allow for full height movement joints to masonry walls as follows: Expansion joints in brickwork typically at maximum 12m crs (6m from corners and returns).

Shrinkage joints in blockwork typically at maximum 6m crs (3m from corners and returns).

For expansion joints in Concrete Bricks refer to manufacturers guidelines, however at no time should joint spacing be greater than 9m (6m typically).

Joint spacing's are based on the provision of a 15mm wide joint incorporating Expandite Expandafoam or equal approved closed cell polyethylene joint filler sealed on external faces with Expandite Thioflex 600 or equal approved elastomeric sealant. Internal finishes must be severed at joints with plaster stops or dry wall stop beads

provided.

Internal walls: provide proprietary IG box lintels to loadbearing internal walls as specified on the drawings or equivalent approved by alternative manufacturer

Provide proprietary IG internal lintel to small openings in non loadbearing blockwork walls or equivalent approved by alternative manufacturer.

All steel lintels to be fully galvanised and have a minimum 150mm bearing to each end unless noted otherwise.

Spacing of Ties Spacing of all ties to comply with the Architects details but to at least comply with the following First row at least one course below DPC at maximum 600mm centres

horizontally, Second and subsequent rows to be spaced at 900mm centres horizontally and 450mm centres vertically in a staggered pattern in bed joints and have a minimum embedment of 50mm (recommend 75mm) into each leaf,

PROPRIETARY ENGINEERED TIMBER FLOOR CONSTRUCTION NOTES.

- Architects & specialists drawings.

- manufacturers details.

manufacturer).

- manufacturer
- unfactored loadings: finishes imposed timber stud pa line load of -

0. Reference should be made to the proprietary floor joist designer/manufacturer details regarding the allowable positioning and sizes of service penetrations through the floor members.

DEAD LOA Self Weight Finishes &

<u>LIVE LOA</u> Live Load Partitions

STAIR LO Live Load Add. Dead

BLOCK W 140 Thick 215 Thick Brick Block

Lintel Schedule					
Reference	Description				
L1	L1 S				
L2	L1 HD				
L3	L1 XHD				
L5	L5 XHD				
L7	BOX				
L8	BOX HD				
3000mm long to	J.N.O. All lintels above be propped to Jidance. All lintels to bear a				

anufacturers guidance. All lintels to bear a minimum of 150mm onto the wall each side.

	Padstone Schedule
Туре	Description

440x215x100 Concrete Padstone P1 P2 660x215x100 Concrete Padstone All Padstones to be precast concrete minimum strength C50.

one side fixed to studs using 3.25mm Nails at 150mm centres max. 'Sole plate' fixed to the floor with 90x90 angle brackets at 1500mm max centres. 'End stud' to be fixed to inner leaf @ 225mm centres internally.

Refer to Architectural drawings and specification for masonry Requirements in respect of acoustic, thermal insulation and durability requirements. The Engineer shall be notified immediately if this conflicts with structural requirements.

Brickwork to have a minimum compressive strength of 20N/mm² and is to comply with BS5628 requirements for CATEGORY 1 of manufacture in accordance with BS EN 771-1 to 6.

Mortar designation as follows: above DPC mortar designation M4

below DPC mortar designation M6

The contractor is responsible and liable for ensuring the stability of the works and services at all stages of construction. The contractor is to note that temporary propping and support is required to the masonry walls during construction until such time as the steelwork bracing and roof structure, with ply decking, are fully completed.

External walls: provide proprietary lintels as specified on the drawings or equivalent approved by alternative manufacturer.

Ties at reveals, openings, movement joints and up the slope of gable walls shall be at maximum 225mm centres vertically.

All structural timber floor members, and framing connections hangers to be designed and manufactured by specialist. Design to be

in accordance with Building Regulations and NHBC Standards. 2. The setting out & dimensions shall be in accordance with the

Timber floor joists shall not be built into party or external wall constructions but shall be supported on proprietary joist hangers to joist suppliers requirements at such locations.

4. All members supported on proprietary hangers to have full contact with the base of the hanger and shall be fixed in accordance with the hanger manufacturers instructions.

5. All members fitted onto steel beams to be supported on proprietary joist hangers to detail by floor joists manufacturer. Where steel beams are specified within the floor depth, the underside of joists shall be 5mm (minimum) below the underside of the beam.

External and party walls parallel with joist spans shall be restrained at top of floor joist level at not more than 2.0m centres in houses and - PHASE 2 1.25m in flats with galvanised 30 x 5.0mm straps extending below top flange for a minimum of 3 joists. Noggins not less than 75% of joist depth and timber blocking adjacent to walls shall be fixed between joists at all strap locations. Straps shall be fixed to members/noggins with not less than 4No. 32 x 3.5mm galvanised sherardised square twisted nails (or alternative detail by joist

All noggins/struts/blockings to be in strict accordance with

8. Overall stability of timber floors during construction to detail by joist

Engineered timber joists to be designed to allow for the following

	refer to Architects details
	1.5 kN/m²
artition loading -	0.5 kN/m ²
-	2.0 kN/m


SUPERSTRUCTURE LOADS:

ADS It Services	By Specialist 0.4 kN/m ²
DS Typical	1.5 kN/m² 0.5 kN/m²
ADING	
	1.5 kN/m²
Load	0.5 kN/m²
ALLS (SHOWN ON ARCH'S D	<u>DRAWINGS)</u>
	2.5 kN/m ²
	4.0 kN/m ²
c Cavity Wall	3.8 kN/m²

GENERAL NOTES

- 1. The drawings, design and all information contained therein are the sole copyright of Richard Jackson Ltd and reproduction in any form is forbidden unless permission is obtained in writing.
- 2. All drawings shall be read in conjunction with all relevant Civil / Structural Engineers drawings, the project specification and Architects, Services Engineers & Landscape Architects drawings.
- For all setting out information, D.P.M., D.P.C., Finishes and waterproofing details refer to the Architects drawings and details.
- The Contractor shall verify all site and setting out dimensions before putting work in hand. Where dimensions are shown on the Engineers drawings, any discrepancies shall be reported to him.
- 5. Dimensions must not be scaled from the Engineers drawings.
- All dimensions are in millimetres unless noted otherwise
- Dimensions marked * are subject to confirmation by site measurement before construction proceeds.
- All dimensions are given to structural surfaces unless noted otherwise
- 9. All lightning connectors to be fixed in accordance with specialist details. 10. No holes, chases, cut-outs, existing or proposed services or the like
- may be formed in or pass through any beam, column, or load bearing wall unless written permission is obtained from the Engineer.
- 11. Holes smaller than 225 x 225mm through slabs are not necessarily shown on the Engineers drawings.
- 12. For size and location of all services refer to the Service Engineers and Architects drawings.
- 13. Inspections made by the Local Authority, NHBC or other Statutory bodies, shall be arranged by the Contractor to suit his programme. Any costs arising out of failing to carry out the work to the satisfaction of the Checking Authority will be the sole responsibility of the Contractor.
- 14. Non-structural fixings are generally not shown on the Engineers drawings and if any such detail is indicated it must be confirmed by cross-reference to other specialists before construction.
- 15. All drawing specifications are given in accordance with NBS (National Building Specification) e.g. E10/130 which refers to NBS Section E10, Clause 130.
- 16. Abbreviations: CRS Centres
- TBC To be confirmed Unless noted otherwise SSL Structural slab level UNO DIA Diameter EGL
- Existing Ground Level FFL FGL Finished Ground Level SOP Setting out point

TOC Top of concrete BOC Bottom of concrete TOS Top of steel Finished Floor Level



This drawing is to be read in conjunction with all other Engineer's drawings and all other project information. Any discrepancy between the Engineer's drawings and other project information is to be reported to the Engineer immediately.




LANSWOOD PARK DEVELOPMENT **BROOMFIELD ROAD**

ELMSTEAD MARKET Drawing Title

HOUSE TYPE 6 SUPERSTRUCTURE FRAMING GENERAL ARRANGEMENT


LANSWOOD LIMITED

	1			rdJ				
Engineering Consultants								
847 The Cra Suit 409, 1 5 Quern Ho 6 The Old C The Wheelh	Alie use, thur	Street, Loi , Mill Court, ch, St Matti	ndon, E1 8 Great Sh hews Rd,	3DE elford, Can Norwich, N	orfolk, NR:	L 1SP	Tel: 01206 2 Tel: 020 744 Tel: 01223 3 Tel: 01603 2 F Tel: 01172 0	8 9910
Email Addre	ess:	mail@rj.uk	.com		Web S	ite: http:/	/www.richardjacks	on.uk.com
Scale 1 : 50				Drawn FM			Date APR 2021	
Project Manager K.TOSH			Checked BGA			Approved		
Status	S	uitability	Descri	ption			RJL Project N 4838	
project		originator	zone	level	type	role	number	revision
48389	9	RJL	XX	GF	DR	S	1006	P02




WINDOW WITH RECONSTITUTED STONE CILL, LINTEL AND STRING COURSE SCALE 1:20 @ A3


HD Homa Design Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR Tel: 01206 272247 Email: homa@homadesign.co.uk Client --Project LANSWOOD PARK ELMSTEAD COLCHESTER CO7 7FD Drawing STRING COURSE, DENTAL BRICK BAND, LINTELS AND BRICK VERGE DETAILS Date NOV 2020 Scale: AS SHOWN Drawing No. DET-01-05 Copyright 🔘 Homa Design Lto



11/05/2022 12:12:04

A FIRST ISSUE APR 21 Date HD Homa Design Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR Tel: 01206 272247 Email: homa@homadesign.co.uk Client --Project LANSWOOD PARK ELMSTEAD COLCHESTER CO7 7FD Drawing HOUSE TYPE 6 (T6) GENERAL ARRANGEMENT ELEVATIONS (OPTION C) Date NOV 2020 Scale: 1:100 @ A3 Drawing No. T6-03-03 A Copyright 🔘 Homa Design Lte Do not scale






	TELESCOPIC AIR BRICK
A INSULATIONS TO FLOOR, WALLS AND ROOF REVISED 07/21 Date Rev Description Date Homa Description Date Architectural & Property Consultants Consultants Collent Tel: 01206 272247 Ital: homa@ehomadesign.co.uk Client Client Project Project LANSWOOD PARK ELMSTEAD COLCHESTER CO7 7FD Drawing SECTION / DETAILS WITH STONE CILL, LINTEL AND STRING BAND SHEET 2 Scale: 1:20 @ A3 Drawing No. DET-01-02 A Copyright @ Homa Design Ltd Do not scale	

NOTE:

METER BOXES TO BE INSTALLED IN ACCORDANCE WITH THE ELECTRICITY PROVIDER


FOR EXACT LOCATION OF METER BOXES REFER TO HOUSE TYPE DRAWINGS.

CONSUMER UNIT TO BE FITTED A MAX OF 2 METRES AWAY FROM THE EXTERNAL METER BOX. IF C U IS FURTHER AWAY AN ISOLATION SWITCH IS REQUIRED TO BE FITTED WITHIN THE METER BOX AND ADJACENT TO THE C U WITH AN ARMOURED CABLE BETWEEN THE TWO UNITS. ALL WORK TO BE APPROVED BY THE ELECTRICITY BOARD.




SECTION THRO' ELECTRIC METER BOX


 Rev Description		 Data
HD Architectural Hyridge, Moo Colchester, Es Tel: 01206 27	Homa Desig & Property Consultan r Road, Langham sex, CO4 5NR 2247 @homadesign.co.uk	711 ats
Client		
Project		
LANSWOOD) PARK	
ELMSTEAD		
COLCHEST	ER CO7 7FD	
	ELECTRIC ME	TED
BOX DETAI		IER
		IER
BOX DETAI		
BOX DETAIL SHEET 6	LS	ER




B INSULATIONS TO FLOOR, WALLS AND 07/21 ROOF REVISED A FIRST ISSUE Rev Description APR 21 Date HD Homa Design Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR Tel: 01206 272247 Email: homa@homadesign.co.uk Email: homa@homadesign.co.uk Client --Project LANSWOOD PARK ELMSTEAD COLCHESTER CO7 7FD Drawing HOUSE TYPE T6 & T6A GENERAL ARRANGEMENT SECTION A-A Date NOV 2020 Scale: 1:20 @ A1 1:40 @ A1 Drawing No. T6-04-01 В Copyright 🔘 Homa Design Lto




A FIRST ISSUE Rev Description APR 21 Date HD Homa Design Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR Tel: 01206 272247 Email: homa@homadesian.co.uk Email: homa@homadesign.co.uk Client --Project LANSWOOD PARK ELMSTEAD COLCHESTER CO7 7FD Drawing HOUSE TYPE T6 & T6A GENERAL ARRANGEMENT FLOOR CARCASSING PLAN Date NOV 2020 Scale: 1:50 @ A3 Drawing No. T6-05-01 A Copyright 🔘 Homa Design Lto not scale







ROOF LAYOUT

THIS DRAWING TO BE READ IN CONJUNCTION WITH ROOF TRUSSES MANUFACTURER'S DRAWINGS AND SPECIFICATION





11/05/2022 12:12:10




PELMET LIGHTNG TO BE PROVIDED TO LANSWOOD'S SPECIFICATION

MANIFOLD AND 13AMP SPUR SOCKET IN BASE UNIT. REFER TO KITCHEN LAYOUT FOR DETAILS


G LIGHTING IN DINING AREA REVISED MAY 22 PELMET LIGHTING NOTE ADDED APR 22 EXTERNAL LIGHT TO FRONT REVISED MAR 22 D EXTERNAL WATER TAP ADDED FFR 22 C PIR LIGHTS ADDED THERMOSTATS ADDED. UTILITY LIGHT REVISED OCT 2 AUG 21 APR 21 FIRST ISSUE **HD** Homa Design Architectural & Property Consu Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR Tel: 01206 272247 Email: homa@homadesign.co.uk Client --Project LANSWOOD PARK ELMSTEAD COLCHESTER CO7 7FD Drawing HOUSE TYPE 6 (T6) GROUND FLOOR PLAN **ELECTRICAL & MECHANICAL** LAYOUT Date NOV 2020 Scale: 1:50 @ A3 Drawing No. T6-07-01 opyright 🔘 Homa De

OTHER	RAWING TO BE READ IN CONJUNCTION WITH ALL PROJECT DRAWINGS AND MANUFACTURER'S ICATIONS/REQUIREMENTS
	TO ROOF LAYOUT FOR SOCKET AND LIGHT EMENT WITHIN ROOF SPACE
SYMBOL	DESCRIPTION
ΔÅ	13 AMP.TWIN SWITCHED SOCKET
Å	13 AMP.SINGLE SWITCHED SOCKET
Å	13 AMP.DOUBLE POLE FUSED SPUR
*	32 AMP.SPUR SWITCHED SOCKET
4	13 AMP.TWIN EXTERNAL SWITCHED SOCK
	TELEPHONE POINT- HIGH SPEED ELECTRONIC NETWORK
▲	TELEVISION POINT
♦	ONE WAY SWITCH
\checkmark	TWO WAY SWITCH
\checkmark	INTERMEDIATE SWITCH
×	NEON SWITCH
0	CEILING LIGHT POINT (DOWNLIGHT) TO SITE SPECIFICATION
\odot	CEILING LIGHT POINT (PENDANT) TO SITE SPECIFICATION
	SENSOR LIGHT
Ø	WALL MOUNTED LIGHT
	REFER TO SITE SPECIFICATION
0	EXTERNAL SURFACE MOUNTED LIGHT MANIFOLD UNITS
(ROOM THERMOSTAT
-	SMOKE DETECTOR
*1 *1	HEAT DETECTOR
*1⊕	CONSUMER CONTROL UNIT
ĒĘ	EXTRACT FAN(REFER TO SPECIFICATION)
<u>لانط</u> ا	
	COMBINED SHAVER AND STRIP LIGHT
++	RADIATOR/TOWEL RAIL

ALL EXTRACTOR FANS TO HAVE ISOLATING SWITCH LOCATION TO BE AREED ON SITE




C B A Rev	ADDED. D1	6 HAND M LIGHT JE	REVISED, THERMOSTAT IED S REVISED	OC-	Г 21 ₹ 21		
Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR Tel: 01206 272247 Email: homa@homadesign.co.uk							
Client							
Project							
LANSWOOD PARK							
ELMSTEAD							
COLCHESTER CO7 7FD							
Drawing HOUSE TYPE 6 (T6) FIRST FLOOR PLAN ELECTRICAL & MECHANICAL LAYOUT							
Date	NOV 2	020	Scale: 1:50 @ A3				
Drav	wing No.	T6-0	07-02		С		
Copyright 🔿 Homa Design Ltd Do not scale							



11/05/2022 12:12:14


A FIRST ISSUE APR 21 HD Homa Design Architectural & Property Consulta Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR Tel: 01206 272247 Email: homa@homadesign.co.uk Client --Project LANSWOOD PARK ELMSTEAD COLCHESTER CO7 7FD Drawing HOUSE TYPES T6 & T6A GENERAL ARRANGEMENT STAIRCASE Date NOV 2020 Scale: AS SHOWN Drawing No. T6-08-01 Copyright 🔘 Homa Des



FRONT ELEVATIONS

SIDE ELEVATIONS

HD Homa Design Architectural & Property Consul Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR Tel: 01206 272247 Email: homa@homadesign.co.uk Client --Project LANSWOOD PARK ELMSTEAD COLCHESTER CO7 7FD Drawing TYPICAL CANOPY DETAILS HOUSE TYPES T1, T2, T3, T6 & T7 SHEET 5 Date NOV 2020 Scale: 1:20 @ A3 Drawing No. DET-01-06 Copyright 🔘 Homa Design Lto



 Rev Descriptio	n		 Date			
HD Homa Design Architectural & Property Consultants Hyridge, Moor Road, Langham Colchester, Essex, CO4 5NR Tel: 01206 272247 Email: homa@homadesign.co.uk						
Client						
Project						
LANSWOOD PARK						
ELMSTEAD						
COLCHESTER CO7 7FD						
Drawing DIAPHRAGM WALL (BRACING WALL) DETAILS						
SHEET 7						
Date NOV 2	020	Scale: 1:20 @ A3				
Drawing No.	DET-	-01-08	-			
Copyright C Homa Design Ltd Do not scale						